

Technical Data:

Supply Voltage : 220V AC or 24V AC-DC
Operation Frequency : 50/60 Hz
Operation Temperature : -5....+55°C
Protection Class : IP 20
Time Range : Specify at the order
Time Sensitivity : ±%1
Relay Contact : 7A - 250V AC (NC+NO)
Dimensions (mm) : 23x82x75 (STR)
 : 30x60x90 (RT)
Net Weight : 92 gr (STR)
 : 100 gr (RT)



| Code (STR or RT) | Adjustable Time Range | Supply Voltage |
|---------------------|--------------------------|----------------------------------|
|06 | 0,1 - 6 sec. | 220V AC 24V AC/DC 50/60 Hz |
|12 | 0,1 - 12 sec. | |
|30 | 0,1 - 30 sec. | |
|60 | 0,1 - 60 sec. | |
|06D | 0,1 - 6 min. | |
|12D | 0,1 - 12 min. | |
|30D | 0,1 - 30 min. | |
|60D | 0,1 - 60 min. | |

- On delay time.
- User friendly front panel design.
- The relay switches when adjusted time is up.
- Single contact out. (NO+NC)

Connection Diagram

A1-A2 : 220V AC **16 (NC) : Normally Closed Contact (1)**
A3-A2 : 24V AC or DC **15 (COM): Common Contact (2)**
 18 (NO) : Normally Open Contact (3)

