

RFM 6X

Technical Data :

Supply Voltage	: 220V-50Hz AC or 24V AC-DC
Operation Voltage	: (0,9-1,1) x Un
Operation Frequency	: 50/60 Hz
Relay Contact	: 7A - 250V AC (NO+NC)
On Time Range	: 0,1 sec - 100 hour (adjustable)
Off Time Range	: 0,1 sec - 100 hour (adjustable)
Operation Temperature	: -5.....+55 °C
Protection Class	: IP 20
Dimensions (mm)	: 23x82x75 (SFR-6X) 30x60x90 (RFM-6X)
Net Weight	: 95 gr. (SFR-6X) 100 gr (RFM-6X)

- Adjustable on-time and off-time .
- On-time adjust with 2 upper roller button.
- Off- time adjust with lower 2 roller button
- Sensitivity adjust with x10 roller buttons.
- Time range between 0,1 sec. - 100 hours.
- Leds show On or off time working.
- Single contacty out. (NO+NC)

Note : When making sensitivity adjustment (x10) roller button uses like division process. For example, to adjust 1 sec. for on-time x10 button must be show 1 and on-time roller button must be show 10s.



Connection Diagram

A1-A2 : 220V AC **16 (NC) : Normally Closed Contact (1)**
A3-A2 : 24V AC or DC **15 (COM): Common Contact (2)**
18 (NO) : Normally Open Contact (3)

