

STR 6X

Technical Data :

Supply Voltage	: 220V AC or 24V AC-DC
Operation Frequency	: 50/60 Hz
Operation Temperature	: -5...+55°C
Protection Class	: IP 20
Time Sensitivity	: ±%1
Time Range	: 0,1 sec - 100 hour (adjustable)
Relay Contact	: 7A - 250V AC (NC+NO)
Dimensions (mm)	: 23x82x75 (STR-6X) 30x60x90 (RTM-6X)
Net Weight	: 94 gr (STR-6X) 100 gr (RTM-6X)



Connection Diagram

A1-A2 : 220V AC **16 (NC) : Normally Closed Contact (1)**
A3-A2 : 24V AC or DC **15 (COM): Common Contact (2)**
 18 (NO) : Normally Open Contact (3)

Selectable Time Range	Sensitivity Adjust (x10)
10 sec.	0,1 - 10 sec
100 sec.	0,1 - 100 sec
10 min.	0,1 - 10 min
100 min.	0,1 - 100 min
10 hour	0,1 - 10 hour
100 hour	0,1 - 100 hour

- User friendly front panel design.
- Time range and Sensitivity adjust convenience.
- Sensitivity adjust with x10 roller button.
- The device starts when it energized and relay switches at the end of adjusted time.

